

Technical Specifications

Model S3030AP	DD334A
Processor & Speed	AMD Athlon XP2000+ 1.67GHz/266
Chipset	VIA KM266
Motherboard	Salsa-GLA
RAM	256/2100 MB DDR SDRAM
Maximum	1 GB (2x512MB DDR SDRAM)
Sockets	Two 184-pin DDR DIMMs
Size	128, 256 and 512 MB DDR DIMMs
Free DIMM Sockets	One
Pairs Required	No
Type Supported	JEDEC unbuffered DDR SDRAM DIMM specification
Cache	128 KB L1, 256 KB L2 Integrated on Processor module
Hard Drive	40 GB
Optical Drive	CD-RW/DVD-ROM Drive 32x10x12x40 32X- Write /10X - Re-write /12x- DVD Read 40X - CD-ROM Read
Average Random Access	DVD = 130 ms / CD-ROM = 110 ms
Transfer Rate	DVD = 21.6 MB/sec / CD-ROM = 6.0MB/sec
Diskette Drive	3.5" (1.44MB)
Fax/Data Modem	V.90 56Kbps
Fax Speed	Up to 14.4Kbps
Data Compression	V.42 bis
Error Correction	V.42
EIA Fax Commands	Class 1
Video Graphics	AGP 4X Graphics
Controller	Integrated w/KM266 Chipset
Video Memory	UMA 64 MB
Network Card	10/100 BaseT, Integrated
MPEG-1/2	MPEG-2 for full-screen, full-motion digital video
Sound	AC'97 Integrated on MB
Controller	Realtek ALC201
Chassis	Chameleon, 250HV PSU
USB Interface Specification	USB 2.0
External Ports	6= USB, 1= serial, 1= parallel
Front I/O Connector	2= USB
Expansion Slots (Total)	3= PCI, 1= AGP
Expansion Slots (FREE)	2= PCI, 1=AGP
Drive Bays (Total)	Two 5.25" external, One 3.5" external, Two 3.5" internal
Drive Bays (FREE)	One 5.25" external, One 3.5" internal
Keyboard/Mouse	One-touch Enhanced Keyboard, PS/2 Optical scrolling mouse